\*\*\*\*







This feature allows for the Casino Staff to quickly replace a printer minimizing downtime. The Exclusive "XPress Connect Technology Key" is a swappable USB key that stores the IP Address and card format required for the AS/400 or Windows to print a card.

The SOLID-510 OC Card Printer with OpenCard Format is an Ideal Solution for Casinos and other Gaming Venues to create Player and VIP Cards, Room Keys and Employee Badges



Hotel • Casino

John Q. Customer

layers Club

xp. Datε

John Q. Customer 1 123456789





- ✓ Ultra-Fast Printing w/ Mag Encoding (6-7 Sec.)

- Exception Card Slot for VIP Cards
- **Quiet Operation**



# SOLID 50 510 PLAYER CARD PRINTER



• New Input Hopper with Exception Card Slot – 200 cards with cover open | 100 cards in default



 Removable -Output Hopper for Kiosks



\*Print Speed : May change under specific condition.



- Front-side Mag Encoding (\*Option)
- Support of Transparent Card
- Support CR79 Type (Factory-installed, \*Option)

- Hot-Swap Technology
- High Speed Printing
- Enhanced FINE™ Imaging Technology
- State-of-the-art CPU
- Reduced Printing Noise
- All-in-one Lock system (\*Option)
- Easy to Handle Laminate Film Cartridge
- Rear-side Stacker for Increased Speed (up to 100 cards, \*Option)



Specifications and availability may change without notice.

# SPECIFICATIONS

Ρ	RΙ	N	ΤI	Ν	G
		ш	ш	ш	~

Print Type Dye-Sublimation
Print Area Edge to Edge
Resolution 300dpi

• Dual Sided Printing Option (with Flipper)

#### CARD

• Card Feeding Automatic

• Card Size ISO CR80 or ISO CR79 (Option-Factory installed)

• Card Thickness 0.38mm (15mil), 1.0mm (40mil)

Card Type
PVC, PET, Composite PVC

### PRINT SPEED

Monochrome 5 sec./card (720 cards/hour)

YMCKO Front-in & Front-out : Max. 17 sec./card (212 cards/hour)

Front-in & Back-out: Max. 16 sec./card (225 cards/hour)

#### CAPACITY

• Input Hopper 100 cards / 200 cards with cover open

Output Hopper
Front: 40 cards / Back: 100 cards (Optional Back-side Stacker)

#### SYSTEM

• Memory 64MB RAM

• Display & Button 2 Line LCD / 2 LED Buttons

• Supported Platforms Microsoft Windows 7/8/10, Mac OS, Linux

Communication USB, Ethernet (Option)

Power Free Voltage (AC100/ 240V, 50~60Hz) / 48W

• Temperature/Humidity  $15{\sim}35\,^{\circ}\mathrm{C}$  /  $35{\sim}70\%$ 

• Security Physical Lock & Kensington Lock (Option)

# DIMENSIONS / WEIGHT

Millimeter (WxLxH)
165 x 390 x 210
Inch (WxLxH)
6.5 x 15.4 x 8.3
Kg/lbs
4.5 / 10

## ENCODING OPTIONS

Magnetic ISO7811 (Track I, II, III Read/Write, HiCo/ LoCo), JIS II
Contact ISO 7816 (ID-1)

• Contactless MIFARE, ISO 14443 (Type A/B), ISO 15693, DESFIRE, iCLASS

**CERTIFICATIONS** 

Authorized Dealer:



Mid-America Business Systems 810 Busch Ct. Columbus, OH 43229 Office: (614) 840-9971 Fax: (614) 840-9981 www.mabsinc.com